Amendments to the Claims

1. (currently amended) A method comprising:

    a)   receiving at least one input through an input device of an ATM which includes a

            cash dispenser, which at least one input comprises a command to determine

            whether a hardware layer or an application layer of the ATM is responsible for at

            least one error in operation of the ATM;

    b)   responsive to the at least input, performing through operation of the ATM at least

            one predefined test function through communication with an <u>extensions for</u>

            <u>financial services (XFS)</u> ~~XFS~~ layer of the ATM, wherein the XFS layer includes

            an application interface portion and a hardware interface portion, wherein the

            application interface portion of the XFS layer is operative to communicate with

            the application layer of the ATM, and wherein the hardware interface portion of

            the XFS layer is operative to communicate with the hardware layer of the ATM;

    c)   determining whether the at least one predefined test function completed

            successfully;

    d)   responsive to the determination in (c), determining through operation of the ATM

            whether the application layer or the hardware layer of the ATM likely causes the

            at least one error in operation of the ATM; and

5

e)   outputting through at least one output device of the ATM indicia representative of

the determination in (d).

2. (original) The method according to claim 1, wherein in (d) when the at least one predefined

test function performs successfully, the determination indicates that the at least one error is likely

caused by the application layer of the ATM, and wherein when the at least one predefined test

function is not performed successfully, the determination indicates that the at least one error is

likely caused by the hardware layer of the ATM.

3. (original) The method according to claim 2, wherein the at least one error in the operation of

the ATM includes an error in the operation of the cash dispenser of the ATM, and wherein in (b)

the at least one predefined test function includes operating the cash dispenser through

communication with the application interface portion of the XFS layer.

4. (original) The method according to claim 3, wherein the application layer of the ATM

includes a user interface application that is operative to output through a display device of the

ATM at least one user interface screen associated with a dispense of cash, wherein the hardware

layer of the ATM includes the cash dispenser and at least one cash dispenser service provider

software component, and wherein in (b) the at least one predefined test function includes

operation of the at least on service provider software component.

6

5. (original) The method according to claim 4, wherein in (b) the user interface application is operative to cause the cash dispenser to operate through communication with the application interface portion of the XFS layer, and wherein the XFS layer is operative responsive to communication with the user interface application to cause the cash dispenser to operate through communication between the hardware interface portion of the XFS layer and the at least one cash dispenser service provider component.

6. (original) The method according to claim 2, wherein the at least one error in the operation of the ATM includes an error in an operation of at least one hardware device of the ATM, and wherein in (b) the at least one predefined test function includes operating the at least one hardware device of the ATM through communication with the XFS layer.

7. (original) The method according to claim 6, wherein the application layer of the ATM includes a user interface application, wherein the hardware layer of the ATM includes the at least one hardware device and at least one service provider software component associated with the at least one hardware device, and wherein in (b) the at lest one predefined test function includes operation of the at least one service provider software component.

8. (original) The method according to claim 7, wherein in (b) the user interface application is operative to cause the at least one hardware device to operate through communication with the application interface portion of the XFS layer, wherein responsive to communication with the user interface application, the XFS layer is operative to cause the at least one hardware device to

7

operate through communication between the hardware interface portion of the XFS layer and the

at least one service provider software component.

9. (currently amended) A method comprising:

a)   performing a plurality of functions with a plurality of hardware devices of an

ATM through communication with an <u>extensions for financial services (XFS)</u>

~~XFS~~ layer of the ATM, wherein the XFS layer includes an application interface

portion and a hardware interface portion, wherein the application interface portion

of the XFS layer is operative to communicate with an application layer of the

ATM, wherein the hardware interface portion of the XFS layer is operative to

communicate with a hardware layer of the ATM;

b)   determining whether each of the functions completed successfully;

c)   determining through operation of the ATM which of the application layer of the

ATM and the hardware layer of the ATM is responsible for at least one problem

associated with the ATM, wherein when all of the functions are performed

successfully, the determination is indicative of at least one problem being

associated with the application layer of the ATM, wherein when at least one of the

functions is performed unsuccessfully, the determination is indicative of the at

least one problem being associated with the hardware layer of the ATM; and

8

d)   outputting through at least one output device of the ATM, a message

representative of the determination in (c).

10. (original) The method according to claim 9, wherein in (a) the plurality of functions include

operation of at least one cash dispenser of the ATM.

11. (original) The method according to claim 9, wherein in (a) the application layer of the ATM

includes a user interface application, wherein the hardware layer of the ATM includes a plurality

of service provider software components in operative connection with hardware devices.

12. (currently amended) A method comprising:

a)   generating at least one error message with an ATM including a cash dispenser

responsive to at least one error associated with operation of the ATM;

b)   receiving at least one input through an input device of the ATM including a

command to determine whether an application layer or a hardware layer of the

ATM likely caused the generation of the at least one error message;

c)   determining through operation of the ATM whether generation of the at least one

error message was likely caused by the application layer or the hardware layer of

the ATM including:

9

BEST AVAILABLE COPY

      i)   performing at least one function with at least one hardware device of the

ATM through communication with an <u>extensions for financial services</u>

<u>(XFS)</u> ~~XFS~~ layer of the ATM; and

      ii)   determining whether the at least one function completed successfully,

wherein when the at least one function completed successfully, the

application layer of the ATM is determined as having likely caused

generation of the at least one error message, and wherein when the at least

one function is not completed successfully, the hardware layer of the ATM

is determined as having likely caused generation of the at least one error

message; and

    d)   outputting through at least one output device of the ATM indicia representative of

the determination in (c).

13. (original) The method according to claim 12, wherein (c) includes operating the cash

dispenser.

14. (original) The method according to claim 12, wherein the application layer of the ATM

includes at least one software application and the hardware layer of the ATM includes the at least

one hardware device of the ATM, and wherein (c) includes operating the at least one hardware

device.

10

15. (currently amended) The method according to claim 14, wherein ~~the application layer of the ATM includes an ODS layer and~~ the hardware layer of the ATM includes at least one service provider software component, <u>wherein the application layer of the ATM includes at least one component adapted to communicate with the at least one service provider software component through communication with the XFS layer,</u> and wherein (c) includes operating the at least one service provider software component.

16. (original) The method according to claim 15, wherein the at least one software application includes a user interface application, and further comprising operating the ATM responsive to the user interface application.

17. (original) The method according to claim 16, wherein in (d) the application layer of the ATM includes a diagnostic application that causes at least one computer of the ATM to output at least one message that is indicative of the determination in (c) through the at least one output device.

18. (currently amended) The method according to claim 16, wherein <u>in</u> (c) the user interface application is operative to cause the at least one hardware device to operate through communication with the XFS layer, wherein the XFS layer is operative to cause the at least one hardware device to operate through communication with the at least one service provider software component.

11

19. (original) Computer readable media bearing instructions which are operative to cause at

least one computer in the machine to cause the machine to carry out the method steps recited in

claim 12.

20. (canceled)

12